



IMPORTANT INSTRUCTIONS

Thank you for purchasing our premium quality automotive floor protection product. To ensure the part is properly protected during shipment we have packed it securely in the box. If required, upon removal from the box, please allow the part to lay flat overnight prior to installing in your vehicle. Position the part on a flat surface in a dry environment with a room or ambient temperature between 65 and 85 degrees F. This will allow the part to relax into the intended shape for a custom fit to your vehicles floor surface. This is especially important in cold climate areas.

Care and Cleaning:

For normal cleaning simply vacuum with non-motorized attachment. For heavy dirt, stains or mud remove the mat from your vehicle and wash with mild household dish soap. Rinse clean with hose. Do not use high pressure sprayers. Allow mat to air dry completely before reinstalling. Do not use heat guns or heated dryers.

I-161 9/25/02



IMPORTANT INSTRUCTIONS

Thank you for purchasing our premium quality automotive floor protection product. To ensure the part is properly protected during shipment we have packed it securely in the box. If required, upon removal from the box, please allow the part to lay flat overnight prior to installing in your vehicle. Position the part on a flat surface in a dry environment with a room or ambient temperature between 65 and 85 degrees F. This will allow the part to relax into the intended shape for a custom fit to your vehicles floor surface. This is especially important in cold climate areas.

Care and Cleaning:

For normal cleaning simply vacuum with non-motorized attachment. For heavy dirt, stains or mud remove the mat from your vehicle and wash with mild household dish soap. Rinse clean with hose. Do not use high pressure sprayers. Allow mat to air dry completely before reinstalling. Do not use heat guns or heated dryers.

I-161 9/25/02