



ULTIMATE

BEDRAIL & TAILGATE CAPS

STEP 1 – PRIOR TO INSTALLATION

- A) Overview:** Bushwacker® only approves installing the TailGate Cap according to these written instructions with the hardware provided. **WARNING:** Failure to install according to these instructions will invalidate the warranty. This includes, but is not limited to using alternative installation methods, hardware, or materials. **DO NOT USE:** Loctite®, Super Glue®, or similar products on the TailGate Cap.
- B) Fit:** Verify the fit of the TailGate Cap to vehicle. *Note: Trimming or modifications to the TailGate Cap may be necessary for use with some Truck Bed Covers or Truck Caps.*
- C) Preparing the Work Area:** Clean the area of installation with a cloth and rubbing alcohol or prep-solvent to remove any car wax or dirt from vehicle surface.
- D) Installation Temperature:** During installation on the vehicle, TailGate Cap and tape need to be between 60°F and 110°F for proper adhesion. Failure to maintain proper installation temperature may result in the part not functioning correctly. If not within acceptable range, increase surface temperature using a heat gun or suitable device (hair dryer) to help reach proper range. The warmer the vehicle surface, the better the initial bond, but should not exceed 110°F.
- E) Care & Cleaning:** Bushwacker TailGate caps are built to last; any detergent you use to wash your vehicle is sufficient to clean the cap. Do not use any harsh abrasive detergents.

I-Sheet# IBW-TGC
Rev-0 02/27/2019

For complete fitment info visit: www.bushwacker.com

TOOLS FOR EASY INSTALLATION:

- Clean Cloth
- Rubbing Alcohol

PLEASE READ: Dirt and debris can become lodged between the tailgate caps and the vehicle's sheet metal, causing scratching and paint wear from vibration. Lund International is not responsible for any damage, and the installation of our tailgate caps is done with the buyer's understanding that this scratching and paint wear may occur.

LIMITED LIFETIME WARRANTY AGAINST ANY MANUFACTURING DEFECTS

- To claim a warranty, you must provide Proof of Purchase.

TailGate Cap Installation Procedures:

STEP 2 – PRIOR TO INSTALLATION

- A) Peel the red vinyl backing partially away from tape pads.** *Note: Make sure the tabs are folded toward the outside of the part and that the middle tape liner is in front of the outside liner. See Illustration #1.*
- B) Carefully lay the part down on the vehicle tailgate and position properly. See Illustration #2.**
- C) Maintaining part placement, begin by pulling middle tape tab first.** Apply downward pressure to part as you remove tape liner. Remove carefully. Do not break tape liner. Repeat for other two tape liners. Once all liners are removed, apply firm pressure along all taped areas. *Note: 3M™ recommends 30 PSI to promote full adhesion. Tape reaches maximum adhesive bond after 24 hours of contact.*



Illustration #1



Illustration #2



The material that your product is made from can be recycled. Please also consider recycling the packaging that your product came in.

